

The Subgrave Curvature I Sub is a subwoofer designed to provide high sound pressure by reinforcing the bass section of Curvature I enclosures.

The system is designed to be stacked.

Curvature I requires a digital processor to maintain optimum performance.

The loudspeaker system has 1 active bass path with a

total of 2 drivers.

For low-frequency reproduction, two 18 "speakers with a 4.5" coil are used in a bass reflex cavity, capable of supporting 1400w of pink noise signal with 6 dB peak for 8 hours (as per eia rs -426 to standard).

The enclosure is constructed of 19mm 13-layer baltic birch wood and is coated with a textured black epoxy paint, which makes it resistant to environmental conditions.

FEATURES

- Very compact and robust
- Excellent for all distances
- Suitable for touring or fixed installations

APPLICATIONS

Reinforcement of sound in theaters.

Live sound reinforcement.

Corporate events.

Fixed installations.

Concert halls.

AUDIO SPECIFICATIONS

Frequency Response	33 Hz to 200 Hz
Low Frequency	1 Enclosure -3 dB @ 40Hz
Power Handling	1400 w Continuous Pink Noise -3Kw
Sensitivity (1w/1m)	101dB
Dispersion	Omnidirectional
Nominal Impedance	4+4Ohm
Drivers	2 x 18" Bass Reflex
Input Connection	EP4 Cannon

MECHANICAL SPECIFICATIONS

Height	140mm
Width	50mm
Depth	57mm
Weight	94kg
Finish	Black Epoxy
Shell	19mm Baltic Birch