

Curvature Systems

CURVATURE MINIWEDGE

Curvature



CURVATURE MINIWEDGE is a passive 2-way stage monitor of high quality and very compact.

It is constructed of 15mm birch plywood and protected against moisture with textured paint

It incorporates two angles of use to increase its versatility and also vessel for tripod.

It has an hanging point M10 at the top

Assemble an 8 "(200mm) low frequency unit with anti-humidity treatment and magnetic neodymium group in a bass reflex box tuned to two low turbulence ports.

For the high frequencies a compression motor of 1.4 "(35mm) of diameter of coil with titanium membrane is used. This transducer is coupled to a horn built in fiber glass and with a dispersion of 60x60°.

Mounts an oversized filter with coils and capacitors of the highest quality

It incorporates 3 speakon connectors in parallel to offer maximum possibilities of connection in any position.

It is possible to combine it with CURVATURE III SUB actively, to achieve an extension of low frequencies up to 40hz



FEATURES

- Very compact and lightweight
- Passive 2-way monitor
- Double angulation for improved versatility
- Tripod Vessel
- Hanging point M10
- Parallel connectors for maximum connection possibilities

APPLICATIONS

- Scenario Monitor
- High Performance Near Field Monitor
- Sound reinforcement in theater or small spaces
- Frontfill
- Fixed installations
- Concert halls

AUDIO SPECIFICATIONS

Frequency Response	75 Hz - 20 KHz
--------------------	----------------

Power Handling	400 w
----------------	-------

SPL Maximum Output	125 dB
--------------------	--------

Sensitivity (1w/1m)	95 dB
---------------------	-------

Dispersion	Horizontal 60° Vertical 60°
------------	-----------------------------

Nominal Impedance	8 Ohm
-------------------	-------

Drivers	LF 8" HF 1"
---------	----------------

Loudspeaker Type	1.8Khz
------------------	--------

Input Connection	3 x Speakon NL2
------------------	-----------------

MECHANICAL SPECIFICATIONS

Height	400mm
--------	-------

Width	220mm
-------	-------

Depth	250mm
-------	-------

Weight	10kg
--------	------

Finish	Black Epoxy
--------	-------------

Shell	15mm Baltic Birch
-------	-------------------

Rigging	Hanging point M10
---------	-------------------